


Technical datasheet

Universal cable with stranded loose tubes for 48 - 144 fibers

U-DQ(BN)H




Order codes: see page 3

b a	Änderung Neuerstellung	22.03.2021 07.09.2017	MW LP	drawn	07.09.2017	LP	 EasyLan® <i>...for a better connectivity</i>			
				appr.	07.09.2017	GF				
				Titel:				EasyLan® Universal cable 48-144 Fibers		Dimensions: mm
				Index				Drawing number:		Original: DIN A4
			ZN-FO171133		Sheet 1 of 3					


Technical Data

Fiber	
Fiber Standard	IEC 60794-2
Core Diameter	Os2 = 9 µm / OM3 ,OM4 = 50 µm
Glass Geometry	
Cladding Diameter	125±0,7 µm
Core-Clad Concentricity	≤ 0,5 µm
Coating Geometry	
Coating Diameter	
48 Fibers	appr. 10,8 mm
72 Fibers	appr. 11,7 mm
96 Fibers	appr. 13,0 mm
144 Fibers	appr. 16,0 mm
Construction	
Installation Temperature	-5°C ~ +60°C
Service Temperature	-30°C ~ +70°C
Storage Temperature	-40°C ~ +70°C
Jacket Color	Os2 = yellow / OM3 = aqua / OM4 = violet
Jacket Material (inside/outside)	FRNC
Cable Weight	
48 Fibers	125 kg/km
72 Fibers	140 kg/km
96 Fibers	150 kg/km
144 Fibers	260 kg/km
Minimum bending radius	
48 Fibers	216 mm
72 Fibers	234 mm
96 Fibers	260 mm
144 Fibers	320 mm
Mechanical Data	
Tensile strength	appr. 3000 N
Compressive strength	3000 N / 10cm
Impact strength	25 Nm
Torsional strength	5 cycles +/-1
Flame resistance	EN 50399 Class Dca

b a	Änderung Neuerstellung	22.03.2021 07.09.2017	MW LP	drawn	07.09.2017	LP		
				appr.	07.09.2017	GF		
Index	Revision code	Date	Name	Titel: EasyLan® Universal cable 48-144 Fibers				Dimensions: mm
Drawing number:				ZN-FO171133				Original: DIN A4
							Sheet 2 of 3	

Order Codes

Article Description	Order Code
FO Universal cable 48 Fibers G50/125 OM3	LUVB48OM3
FO Universal cable 72 Fibers G50/125 OM3	LUVB72OM3
FO Universal cable 96 Fibers G50/125 OM3	LUVB96OM3
FO Universal cable 144 Fibers G50/125 OM3	LUVB144OM3
FO Universal cable 48 Fibers G50/125 OM4	LUVB48OM4
FO Universal cable 72 Fibers G50/125 OM4	LUVB72OM4
FO Universal cable 96 Fasern G50/125 OM4	LUVB96OM4
FO Universal cable 144 Fibers G50/125 OM4	LUVB144OM4
FO Universal cable 48 Fibers E09/125 OS2	LUVB48OS2
FO Universal cable 72 Fibers E09/125 OS2	LUVB72OS2
FO Universal cable 96 Fibers E09/125 OS2	LUVB96OS2
FO Universal cable 144 Fibers E09/125 OS2	LUVB144OS2

				drawn	07.09.2017	LP	
				appr.	07.09.2017	GF	
b a	Änderung Neuerstellung	22.03.2021 07.09.2017	MW LP	Titel:			
				EasyLan® Universal cable 48-144 Fibers			
Index	Revision code	Date	Name	Drawing number:			Dimensions: mm
				ZN-FO171133			Original: DIN A4
							Sheet 3 of 3